




Standards	Required Value	Avg. Value
 ISO 10545 / 3 Water Absorption	Grupo B1 A / E < 0,5%	Meets requirements
 ISO 10545 / 4 Modulus of Rupture	> 1300 N	Meets requirements
 ISO 10545 / 5 Bending strength	> 35 N/mm <sup>2</sup>	Meets requirements
 ISO 10545 / 7 Resistance to abrasion (PEI)	Between I - V	White / Grey IV Graphite III
 ISO 10545 / 12 Frost resistance	Resistant	Meets requirements
 ISO 10545 / 13 Chemical resistance	Min. GB / GLB	Meets requirements
 ANSI A 137.1-2012 DCOF Slip resistance	Wet ≥ 0.42	Wet ≥ 0.42
 ANSI A 137.1-2012 SCOF Slip resistance	Wet ≥ 0.60 Dry ≥ 0.70	Wet ≥ 0.60 Dry ≥ 0.70

1/2 BROKEN JOINT NOT RECOMMENDED.  
MANUFACTURE RECOMMENDS 1/3 OR  
LESS STAGGERED SPACING

**IMPORTANT**



NO



YES



**CONTEMPO**  
PORCELAIN

# CONTEMPO

PORCELAIN

## CONTEMPO GRAPHITE



15" x 30"  
Rectified Edge



12" x 24"  
Rectified Edge



MOSAIC 1.25" x 4"  
(12"x12" sheet)



BULLNOSE 3"x 12"


## CONTEMPO GREY




15" x 30"  
Rectified Edge



12" x 24"  
Rectified Edge



MOSAIC 1.25" x 4"  
(12"x12" sheet)



BULLNOSE 3"x 12"


## CONTEMPO WHITE



15" x 30"  
Rectified Edge



12" x 24"  
Rectified Edge



MOSAIC 1.25" x 4"  
(12"x12" sheet)



BULLNOSE 3"x 12"

CONTEMPO GRAPHITE

CONTEMPO GREY

