



	TECHNICAL DATAS	STANDARD	REQUIRED VALUE UNI EN 14411 - BI a	bambù
	Thickness	10545.2	±5%	10,5 mm ±5%
	Water absorption	10545.3	≤0,5%	≤0,15%
	Bending strength	10545.4	≥35 N/mm <sup>2</sup>	≥40 N/mm <sup>2</sup>
	Frost resistance	10545.12	No sample must show guaranteed cracks in or considerable alteration of the surface	Frost-Proof
	Stain resistance	10545.14	CLASS ≥3	CLASS 5
	Hardness in Mohs degrees	UNI EN 101	≥5° MOHS	7
	Chemical strength	10545.13	Resistance to low concentrations of alkalis and acids Resistance to high concentrations of alkalis and acids Resistance to household chemical products and swimming-pool additives (60 min)	GLA GHA GA
	Slip resistance	ASTM C-1028	DRY >0,6 WET >0,6	DRY >0,73 WET >0,60

#### Shade Variation Guideline



**V2**  
Slight variations



#### Contribute to LEED certification point

##### RECYCLED CONTENT, MR Credit 4.1 (1 LEED point)

BAMBU is manufactured using recycled products. The percentage of these recycled materials is: 17% (PRE-CONSUMER materials).

##### VOC CONTENT, EQ -4.2 (1 LEED point)

BAMBU is completely without VOC (Volatile Organic Compounds). Therefore, won't give off VOC during its use, in any operating conditions.

Ceramic Tiles of Italy



**HAPPY FLOORS**



# bambù

Full Body Porcelain





# bambù


Full Body Porcelain



**GRIGIO** - 12"x 24"  
PEI V



1.5"x 3" Mosaic  
(12"x 12" Sheet)




Bullnose - 3"x 12"



**NERO** - 12"x 24"  
PEI IV



1.5"x 3" Mosaic  
(12"x 12" Sheet)



Bullnose - 3"x 12"



**AVORIO** - 12"x 24"  
PEI V



1.5"x 3" Mosaic  
(12"x 12" Sheet)



Bullnose - 3"x 12"



**BEIGE** - 12"x 24"  
PEI V



1.5"x 3" Mosaic  
(12"x 12" Sheet)



Bullnose - 3"x 12"