












TECHNICAL CHARACTERISTICS		REFERENCE STANDARD	REQUIRED VALUE	AV. MANUFACTURE VALUE										
	DIMENSIONS	ISO 10545-2	Compliant	Compliant										
	WATER ABSORPTION	ISO 10545-3	≤0,5 %	<0,1%										
	MODULUS OF RUPTURE	ISO 10545-4	MODULUS OF RUPTURE R ≥ 35 N/mm ² BREAKING STRENGTH S ≥ 1300 N	R>50 N/mm ² S>2500 N										
	SCRATCH RESISTANCE	ISO 10545-7	0 - V	IV										
	LINEAR THERMAL EXPANSION	ISO 10545-8	=< 9x10 ⁻⁴ °C ⁻¹	6x10 ⁻⁴ °C ⁻¹										
	THERMAL SHOCK RESISTANCE	ISO 10545-9	Resistant	Resistant										
	FROST RESISTANCE	ISO 10545-12	Resistant	Resistant										
	ACID AND ALKALI RESISTANCE	ISO 10545-13	CLASS GB MIN.	Low concentration GLA High concentration GHA										
	CHEMICAL RESISTANCE	ISO 10545-13	CLASS GB MIN.	GA										
	STAIN RESISTANCE	ISO 10545-14	CLASS 3 MIN.	5										
	FRICTION COEFFICIENT (SLIPPERINESS)	<table border="1"> <tr> <td colspan="2">CTE - Spain UNE-EN 12635-2003</td> <td colspan="2">ASTM - USA ASTM C1028</td> <td>DIN - Germania DIN 51130</td> </tr> <tr> <td>Class 1</td> <td>15<Rd<=35</td> <td>Dry neolythe 0,65</td> <td>Wet neolythe 0,60</td> <td>R9 ZH 1/571</td> </tr> </table>			CTE - Spain UNE-EN 12635-2003		ASTM - USA ASTM C1028		DIN - Germania DIN 51130	Class 1	15<Rd<=35	Dry neolythe 0,65	Wet neolythe 0,60	R9 ZH 1/571
CTE - Spain UNE-EN 12635-2003		ASTM - USA ASTM C1028		DIN - Germania DIN 51130										
Class 1	15<Rd<=35	Dry neolythe 0,65	Wet neolythe 0,60	R9 ZH 1/571										

THE PRODUCTS HAVING AN ABSORPTION < 0,5% ARE CLASSIFIED ACCORDING TO THE UNI STANDARDS "FULLY VITRIFIED TILES" AND ACCORDING TO THE ASTM STANDARDS "IMPERVIOUS TILES"



HAPPY FLOORS

www.happy-floors.com



AMAZONAS
PORCELAIN 8" x45"



AMAZONAS BLANC



AMAZONAS NUDE



AMAZONAS TEJA



MANUFACTURE RECOMMENDS 1/3 OR LESS STAGGERED SPACING FOR LINEAR & LARGE FORMAT SIZE

SPECIAL ATTENTION & CARE MUST BE USED WHEN INSTALLING A LINEAR SIZE PATTERN TO AVOID LIPPAGE

AMAZONAS BLANC

8"x45" Rectified Edge



Bullnose 4"x22,5"

AMAZONAS NUDE



8"x45" Rectified Edge



Bullnose 4"x22,5"


AMAZONAS TEJA

8"x45" Rectified Edge




Bullnose 4"x22,5"


GROUT JOINT REQUIRED FOR RECTIFIED EDGE TILE (Recommended installation patterns)




8"x45"



8"x45"



8"x45"



8"x45"

IMPORTANT Please note that fixing in a 50% staggered configuration is not recommended. We suggest the following fixing configurations for these ceramic materials:

NO 50%



YES 15%

