



JAIPUR			
Technical Specifications	Reference Standard	Standard Requirements	Test Results
Water Absorption	UNI EN ISO 10545-03	< 0.5 %	Meets requirements
Breaking Strength	UNI EN ISO 10545-04	Minimum: 1300 N	>1300 N
Modulus of Rupture	UNI EN ISO 10545-04	Minimum: 35 N/mm ²	> 35 N/mm ²
Shock Resistance	UNI EN ISO 10545-08	Suggested Minimum: e > 0.55	> 0.55
Resistance to Deep Abrasion	UNI EN ISO 10545-09	Maximum: 175 mm ³	175 mm ³
Thermal Shock Resistance	UNI EN ISO 10545-09	Resistant	Meets requirements
Frost Resistance	UNI EN ISO 10545-12	As Reported	Meets requirements
Chemical Resistance	UNI EN ISO 10545-13	Domestic Chemical Products: UBT / U3 Acids and Alkalis: As Reported	CLA / GMA CA
Stain Resistance	UNI EN ISO 10545-14	Minimum: Class 3	Class 3
PEI Rating (Scratch Resistance)	ASTM D 1507	As Reported	IV
Dynamic Coefficient of Friction (DCOF)	AAS 1107-1	Per Local Building Codes. Referential to the Finished Look (Final Wet) : -> 0.42	>0.42
Shade Variation	Not Available	As Reported	V.2
Thickness	Not Available	As Reported	9mm
Number of Screens	Not Available	As Reported	30

1/2 BROKEN JOINT NOT RECOMMENDED



MANUFACTURER RECOMMENDS 1/3 OR LESS STAGGERED SPACING



HAPPY FLOORS
www.happy-floors.com



Jaipur

FULL-BODY PORCELAIN



Blanc




15\"/>



12\"/>



3\"/>



2\"/>



Hexagon Mosaic
12\"/>

Tanned




15\"/>



12\"/>



3\"/>



2\"/>



Hexagon Mosaic
12\"/>


Midnight



15\"/>



12\"/>



3\"/>



2\"/>



Hexagon Mosaic
12\"/>